



Desktop survey undertaken from google street view with imagery dated March 2023

All traffic management shall comply with all current legislation and guidance including Chapter 8, Safety at Street Works and Road Works (A Code of Practice)

Pedestrian management to be installed and managed to suit site conditions in accordance with current legislation & codes of practice by the contractor unless otherwise stated

All signage and road markings shall conform with the Traffic Signs Regulations and General Directions (TSRGD).

Sign locations are indicative only, exact location to be determined on site.

Suitably qualified operative to assess site to ensure the installation complies with all current legislation. Any issues and/or changes from the original design should be immediately reported to the relevant contracts manager/designer.

This design is only valid for 12months from date of production and should be re-evaluated if installation is to take place after this period.

SIGN SCHEDULE

Q1.1 Ref 134361040 Road Ahead Closed	
Q1.2 Ref 2202 Diverged traffic ENDS	
Q1.3 Ref 2202 Diverged traffic	
Q1.4 Ref 517 Road works on one side only (width 400yds)	
Q1.5 Ref 517 400 yds	
Q1.6 Ref 517 200 yds	
Q1.7 Ref 517 200 yds	
Q1.8 Ref 517 200 yds	
Q1.9 Ref 517 200 yds	
Q1.10 Ref 517 200 yds	
Q1.11 Ref 517 200 yds	
Q1.12 Ref 517 200 yds	
Q1.13 Ref 517 200 yds	
Q1.14 Ref 517 200 yds	
Q1.15 Ref 517 200 yds	
Q1.16 Ref 517 200 yds	
Q1.17 Ref 517 200 yds	
Q1.18 Ref 517 200 yds	
Q1.19 Ref 517 200 yds	
Q1.20 Ref 517 200 yds	
Q1.21 Ref 517 200 yds	
Q1.22 Ref 517 200 yds	
Q1.23 Ref 517 200 yds	
Q1.24 Ref 517 200 yds	
Q1.25 Ref 517 200 yds	
Q1.26 Ref 517 200 yds	
Q1.27 Ref 517 200 yds	
Q1.28 Ref 517 200 yds	
Q1.29 Ref 517 200 yds	
Q1.30 Ref 517 200 yds	
Q1.31 Ref 517 200 yds	
Q1.32 Ref 517 200 yds	
Q1.33 Ref 517 200 yds	
Q1.34 Ref 517 200 yds	
Q1.35 Ref 517 200 yds	
Q1.36 Ref 517 200 yds	
Q1.37 Ref 517 200 yds	
Q1.38 Ref 517 200 yds	
Q1.39 Ref 517 200 yds	
Q1.40 Ref 517 200 yds	
Q1.41 Ref 517 200 yds	
Q1.42 Ref 517 200 yds	
Q1.43 Ref 517 200 yds	
Q1.44 Ref 517 200 yds	
Q1.45 Ref 517 200 yds	
Q1.46 Ref 517 200 yds	
Q1.47 Ref 517 200 yds	
Q1.48 Ref 517 200 yds	
Q1.49 Ref 517 200 yds	
Q1.50 Ref 517 200 yds	
Q1.51 Ref 517 200 yds	
Q1.52 Ref 517 200 yds	
Q1.53 Ref 517 200 yds	
Q1.54 Ref 517 200 yds	
Q1.55 Ref 517 200 yds	
Q1.56 Ref 517 200 yds	
Q1.57 Ref 517 200 yds	
Q1.58 Ref 517 200 yds	
Q1.59 Ref 517 200 yds	
Q1.60 Ref 517 200 yds	
Q1.61 Ref 517 200 yds	
Q1.62 Ref 517 200 yds	
Q1.63 Ref 517 200 yds	
Q1.64 Ref 517 200 yds	
Q1.65 Ref 517 200 yds	
Q1.66 Ref 517 200 yds	
Q1.67 Ref 517 200 yds	
Q1.68 Ref 517 200 yds	
Q1.69 Ref 517 200 yds	
Q1.70 Ref 517 200 yds	
Q1.71 Ref 517 200 yds	
Q1.72 Ref 517 200 yds	
Q1.73 Ref 517 200 yds	
Q1.74 Ref 517 200 yds	
Q1.75 Ref 517 200 yds	
Q1.76 Ref 517 200 yds	
Q1.77 Ref 517 200 yds	
Q1.78 Ref 517 200 yds	
Q1.79 Ref 517 200 yds	
Q1.80 Ref 517 200 yds	
Q1.81 Ref 517 200 yds	
Q1.82 Ref 517 200 yds	
Q1.83 Ref 517 200 yds	
Q1.84 Ref 517 200 yds	
Q1.85 Ref 517 200 yds	
Q1.86 Ref 517 200 yds	
Q1.87 Ref 517 200 yds	
Q1.88 Ref 517 200 yds	
Q1.89 Ref 517 200 yds	
Q1.90 Ref 517 200 yds	
Q1.91 Ref 517 200 yds	
Q1.92 Ref 517 200 yds	
Q1.93 Ref 517 200 yds	
Q1.94 Ref 517 200 yds	
Q1.95 Ref 517 200 yds	
Q1.96 Ref 517 200 yds	
Q1.97 Ref 517 200 yds	
Q1.98 Ref 517 200 yds	
Q1.99 Ref 517 200 yds	
Q1.100 Ref 517 200 yds	

Key:

	Works Area		Temporary Traffic Signal
	Closure		Stop & Go Board
	Vehicle Diversion Route		Temporary Ped Signal
	Ped Diversion Route		Existing Bus Stop
	Cone		Temporary Sign
	Datum Point		Pedestrian Barrier

Safety Information:

Min width of sideways safety zone (S)	0.5m
Min length of laneways clearance (L)	15m
Norton Road	49

Site Information:

NSG	Norton Road Broomhill
Local Authority	Worcestershire
USPN	45400961
Road Type	Single lane carriageway
Works Location	X:386348 Y:252022
Surveyed	X Bus Stop(s) X Parked Vehicles X
Permit Signals	X Controlled X Cycle Lanes X

Chapter 8 details:

Detail B (9)

- Single/Dual carriageway 40mph or less - 450mm traffic cones.
- Single/Dual carriageway 50mph or more - 750mm traffic cones.
- Dual carriageway national speed limit - 750mm traffic cones.
- relaxation 3m.

Notes:

- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
- 50 tapered taper cones should be used in accordance with Table A1.3 (Appendix 1).
- 50 tapered taper cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

Detail C1 (5)

- Single/Dual carriageway 40mph or less - 450mm traffic cones.
- Single/Dual carriageway 50mph or more - 750mm traffic cones.

Notes:

- During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

Working in Partnership with

traffix

Old Arden Brickworks | Balsall Hall | Solihull West Midlands | B92 0DY
 1+44 (0)800 819 8001 | 1+44 (0)1915 442507
 info@traffix.com | www.traffix.com

OROUNDWORKS SPECIALISTS
 FOUNDATIONS SPECIALISTS LTD

Project title: Traffic Management

Drawing title: Proposed Road Closure Norton Road Worcester

Project Number: WRS 2PF

Date:	13/12/2023	Scale:	NTS	Paper:	A2
Drawn:	CM	Checked:	CM	Approved:	MS
Project Number:	001	Drawing Number:	-	Revision:	-

This drawing is copyright & the property of Traffix & must not be copied in whole or in part without the written permission. Copyright is reserved. © The Contractor is to report all discrepancies & errors to the Contract Manager prior to works commencing.